

# P7290 PROJECTOR

## DLP Technology – Professional Series

The Acer P7290 projector is equipped with leading technologies for high-impact, professional business presentations. This DLP® certified projector provides bright, lifelike visuals and guarantees big power savings, thanks to Acer ePower Management technology.

### Why a P7290 Projector?

- Native Resolution XGA (1,024 x 768), Maximum UXGA (1,600 x 1,200), WSXGA+ (1,680 x 1,050)
- Contrast Ratio 3000:1
- Brightness 5,000 ANSI Lumens (STD), 4,000 ANSI Lumens (ECO)
- Projection Distance 3.9' (1.2m) ~ 31.4' (9.6m)
- PIP support



# Technical Specification

<b>Model Name</b>	P7290
<b>Resolution</b>	Native XGA (1,024 x 768) Maximum UXGA (1,600 x 1,200), WSXGA+ (1,680 x 1,050)
<b>Computer Compatibility</b>	IBM PC and Compatibles, Apple iMac/MacBook, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
<b>Video Compatibility</b>	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
<b>Aspect Ratio</b>	4:3 (Native), 16:9
<b>Contrast Ratio</b>	3000:1
<b>Displayable Colours</b>	1.07 Billion Colours
<b>Brightness</b>	5,000 ANSI Lumens (Standard), 4,000 ANSI Lumens (ECO)
<b>Projection Lens</b>	F = 2.52 ~ 2.79, f = 22.55mm ~ 27.06mm 1:1.2 Manual Zoom and Manual Focus
<b>Projection Screen Size</b>	31" (79cm) ~ 300" (762cm)
<b>Projection Distance</b>	3.9' (1.2m) ~ 31.4' (9.6m)
<b>Throw Ratio</b>	63"@2m (1.57 ~ 1.89:1)
<b>Horizontal Scan Rate</b>	27 ~ 92 kHz
<b>Vertical Scan Rate</b>	50 ~ 85 Hz
<b>Lamp Type / Life</b>	Philips 350 W user replaceable P-VIP lamp / 2,000 Hours (Standard), 3,000 Hours (ECO)
<b>Keystone Correction</b>	+/-40 Degrees (Vertical), +/-15 Degrees (Horizontal)
<b>Projection Mode</b>	Front, Rear, Front Ceiling, Rear Ceiling
<b>Ceiling Mounting Capability</b>	Yes
<b>Audio</b>	Two Internal Speaker with 3 watts Output
<b>IR Remote Control</b>	IR & wired remote control with laser pointer & mouse & PgUp/PgDn functions
<b>Digital Zoom</b>	8X
<b>Power Supply</b>	AC Input 100-240V auto-switching power supply
<b>Power Consumption</b>	460 Watts (Operation), 1 Watt (Standby)
<b>Operating Temperature</b>	5°C ~ 35°C / 41°F ~ 95°F
<b>Noise Level</b>	35 dBA (Standard mode), 29 dBA (ECO mode)- w/o dust filter
<b>Input Interface</b>	Analog RGB/Component Video (D-sub) x 2, Composite Video (RCA) x 1, S-Video (Mini DIN) x1, Component (3 RCA) x 1, HDMI (Video, Audio, HDCP) x 1, DVI (HDCP) x 1, PC Audio (Stereo mini jack) x 2
<b>Output Interface</b>	Analog RGB (D-sub) x 1, PC Audio (Stereo mini jack) x 1, SPDIF Audio (RCA) x 1
<b>Control Interface</b>	USB (Type B) x 1, RS232 (Mini DIN) x 1, Wired remote control port (Mini jack) x 1
<b>Weight and Dimensions</b>	12 lbs (5.4Kg) / 404 x 315 x 120 mm (15.9" x 12.4" x 4.7")
<b>Compliance</b>	C-Tick (AS/NZS 60950)
<b>Standard Accessories</b>	AC power cord, VGA cable, Composite video cable, DVI cable, S-Video cable, Component cable, Remote control, Battery x 2 for remote control, Detachable cable holder, Duster filter x 2, Lens cap, Carrying case, User's guide (CD-ROM), Quick start guide, Security card
<b>Standard Warranty</b>	2 year return to base

Product specifications are subject to change without prior notice. Acer & the Acer logo are registered trademarks of Acer Inc., and Acer America Corp. All other products, brand names, or company names are trademarks & registered trademarks of their respective companies. Acer shall not be liable for technical, editorial or pictorial errors, inaccuracies or omissions contained herein; nor for any consequential damage resulting from the furnishing, performance, or use of this material. \* Maximum hours. Actual hours depend on usage and configuration. \*\* Contact Acer for warranty details.

**JUST PROJECTORS**

Suite 4, Ferndale Court, West End Road  
Mortimer, Berkshire, RG7 3SY  
Tel: 0118 907 0703  
Web: [www.projectors.co.uk](http://www.projectors.co.uk)