

PLC-WXU30B

Native Widescreen Projector



Available December 2007

- ◆ Native WXGA (1280 x 800)
- ◆ 3700 ANSI Lumen, plus Eco Mode
- ◆ Contrast Ratio 500:1
- ◆ DVI-I Input (HDCP Compliant)
- ◆ 1x Dsub15 Data Input, plus 1x Monitor Re-drive
- ◆ Optical Zoom (Throw 1.25-1.95:1)
- ◆ Auto Input Search
- ◆ RJ45 Port for Networking
- ◆ Integrated Audio Alarm
- ◆ Auto Digital Keystone
- ◆ Wireless Remote with Laser Point
- ◆ Weight 3.6 kg

Model name	PLC-WXU30B
Panel	0.74inch P-Si TFT active matrix type x 3
Native Resolution	1280 x 800 (16:10)
Projection lamp	275W
Brightness (typical)	3700 ANSI lumens
Uniformity	85% (corner to centre)
Contrast ratio	500:1
Up-Down ratio	9:1, Digital Keystone \pm 40° vertical
Projection lens	F1.7 ~ 2.5, f=19.2 ~ 30.2 mm
Screen size	40" ~ 300" 0.99wide ~ 12.1tele (m) 100" at 2.5 ~ 4.0m
AV Signal	Input: Dsub15 for Component S-Video (Mini DIN 4 Pin) Composite (RCA)
Color systems	PAL / SECAM / NTSC / NTSC4.43 / PAL-M/N
PC Signal	Input: DVI-I(HDCP compliant) Dsub15 2 nd Data Input Monitor Re-drive
Audio	RCA (L/R) for Video Mini Jack (Stereo) for Computer Input Mini Jack (Stereo) for output (Variable)
Control Port	Mini-DIN 8-pin
Computer compatibility	(UXGA/WXGA)/SXGA/XGA/SVGA/VGA/MAC
Scanning frequency	H/V sync 15kHz~100kHz, 50Hz~100Hz Dot clock 140 MHz
Sound output	1W mono
Voltage	100V-240V AC (auto voltage)
Dimensions(W x H x D)	334 x 78 x 257mm
Weight	3.6Kg