



PLC-XW200

- Brightness: 2200 ANSI Lumens
- Resolution: XGA (1024 x 768)
- 2 x Data, 1 x Video
- Network Control and Monitoring
- Auto Set up
- PIN code security
- Weight: 2.5kg


PLC-XW200

TECHNICAL DETAILS	PLC-XW200
Category	Business & Education
Panel	3 x 0.55" TFT Polysilicon (4:3)
Lamp	220W UHP
Brightness ANSI lumens	2200
Lamp Service Life	3000h (Eco Mode), 2000h (Normal Mode)
Fan Noise	29dBA (Eco Mode), 34dBA (Normal Mode)
Standard Lens	F= 2.00 - 2.15, f= 18.38 – 22.06mm
Throw Distance Ratio	1.62 – 1.92:1
Throw Distance	1.3m – 11.8m
Contrast Ratio	500:1
Resolution in pixels	786,432 (1024 x 768)
Image size min-max (diagonal)	40" – 300"
Uniformity	85%
Bandwidth/Frequency	140MHz, Horizontal 15kHz – 100kHz, Vertical 50Hz – 100Hz
Colour Systems	NTSC / PAL / SECAM / NTSC4.43 / PAL-M / PAL-N
Connections	Inputs: 1 x D-sub 15 (component, S-Video) 1 x D-sub 15 (Analogue RGB, Monitor out) 1 x RCA (Composite Video) 1 x Mini Jack (Computer Audio in) 1 x Mini Jack (Variable Audio Out) 1 x RJ45 (Network control and Monitoring) 1 x Dsub9 (Control port)
Keystone Correction	Vertical $\pm 30^\circ$
HDTV Signals	1080i/50, 1080i/60, 1035i, 720p
Computer Compatibility	UXGA / WXGA / SXGA+ / SXGA / XGA / SVGA / VGA / MAC
Zoom/Focus	1.2x / Manual
Power Consumption/Voltage	203w (Eco Mode), 258 (Normal Mode), 0.7W (Standby Mode)
Warranty	3 Year
Dimensions (W x H x D)	333.5 x 94.2 x 247mm
Weight	2.5kg
Standard Accessories	Quick Reference Guide, Owner Manual (CD ROM), Network Software (CD ROM), Power Cable, Remote Control
Optional Accessories	POA-CA-COMPVGA (Component-VGA cable), POA-CA-VGAS (S-Video-VGA Cable), POA-CA-SCART (Scart-VGA Cable)

* You can use the distance calculator at <http://uk.sanyo.com> to determine exact image sizes and distances



Technical specifications subject to change without notice. Status 02/2009



Telephone: 01923 246363

Email: info@sanyo.co.uk

Visit: <http://uk.sanyo.com>