

JUST PROJECTORS


Key Features

- LED technology with 30,000 hours lifespan
- Instant power on/off for efficient use
- 3,000 LED Lumens offering bright images in any environment
- 360° projection for versatile application
- Convenient projector software updates via USB connection



Product **Description**

The LS500WH is ViewSonic's first lamp-free, 3,000 LED Lumens high brightness WXGA projector for business and education. Adopting industry-leading LED technology, it frees users from frequent lamp replacement and toxic mercury for a safer and greener environment, offering phenomenal lifespan of 30,000 hours and true-to-life colours with 125% Rec.709. Give light to your presentations effortlessly with efficient instant power on/off and 360° tilt angle projection for flexible setup in small-to-medium-sized meeting rooms/classrooms.





SPECIFICATION

OTHERS

SPECIFICATION		OTHERS	
Native Resolution:	1280x800	Power Supply Voltage:	100-240V+/- 10%, 50/60Hz(AC in)
DMD Type:	DC3		Normal: 156WStandby:
Brightness:	3000 (LED Lumens)	Power Consumption:	<0.5W
Contrast Ratio:	3000000:1	Operating Temperature:	0~40°C
Display Colour:	1.07 Billion Colours	Net Weight:	2.45kg
Light Source Type:	LED	Dimensions (WxDxH) with Adjustment Foot:	293x221x115mm
Light Source Life (hours) with Normal Mode:	up to 30000	OSD Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Hungarian. Total 24 languages
Lamp Watt:	RGB LED		
Lens:	F=2.56-2.68, f=22- 24.1mm		
Projection Offset:	100%+/-5%		
Throw Ratio:	1.55-1.70		
Optical Zoom:	1.1X		
Digital Zoom:	0.8x-2.0x	STANDARD ACCESSORY	
Image Size:	30"-300"	Power Cord:	1
Throw Distance:	1m- 10.98m(100"@3.34m)	Remote Control:	1
Keystone:	+/- 40° (V)	QSG:	Yes
Audible Noise (Normal):	30dB	OPTIONAL ACCESSORY	
Audible Noise (Eco):	26dB	Wall/Ceiling Mount:	PJ-WMK-007
Input Lag:	16ms	Carry Bag:	PJ-CASE-008
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)		
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p		
Video Compatibility:	NTSC, PAL, SECAM		
Horizontal Frequency:	15K-102KHz		
Vertical Scan Rate:	23-120Hz		
INPUT			
HDMI:	1(HDMI 1.4/ HDCP 1.4)		
Audio-in (3.5mm):	1		
OUTPUT			
Audio-out (3.5mm):	1		
Speaker:	2W		
USB Type A (Power):	1 (5V/2A)		
CONTROL			
RS232 (DB 9-pin male):	1		

Copyright $\ensuremath{\mathbb{C}}$ ViewSonic Corporation 2000-2022. All rights reserved.