
# Key **Features**

- Ultra Fine Touch Technology offering up to 40-point touch for a pen-on-paper writing experience
- myViewBoard Whiteboard software with engaging classroom tools
- Screen share via USB-C or wirelessly via myViewBoard Display and ViewBoard Cast with Airplay and Chromecast
- Intuitive remote device control and multimedia broadcast
   with myViewBoard Manager
- Android 11 OS powered by an octacore CPU for optimised efficiency and security



# Product **Description**

Designed with modern educators in mind, the ViewBoard® 50-5 Series offers an intuitive and interactive interface for a multi-user writing experience. With a single-cable USB-C for instant, worry-free connectivity, teachers can seamlessly plug-in and control their devices while continuing the lesson. Both students and educators enjoy smooth writing with Ultra Fine Touch Technology offering 40-point touch, and the dual-pen that comes in a range of colours and sizes. Rest assured you and your students' eyes are cared for and protected as the ViewBoard® 50-5 Series comes with Flicker-Free technology and an integrated TÜV certified blue light filter for all brightness levels. Fully integrated with the myViewBoard suite, the ViewBoard® 50-5 Series brings together hardware and software for a complete classroom solution. Compatible with a full line of accessories, the ViewBoard® 50-5 Series enables you to effectively teach with a variety of engaging tools.



65"  TFT LCD Module with DLED Backlight.IPS  1428.48(H) × 803.52(V)  16:9  UHD 3840x2160  1.07B colors (10bit)  350 nits (typ.)  1200:1 (typ.) 5000:1 (DCR)  8ms  H = 178, V = 178 typ.  50,000 hours (Min)  Hardness: 7H, Anti-glare coating  Slim  Landscape
TFT LCD Module with DLED Backlight.IPS  1428.48(H) × 803.52(V)  16:9  UHD 3840x2160  1.07B colors (10bit)  350 nits (typ.)  1200:1 (typ.) 5000:1 (DCR)  8ms  H = 178, V = 178 typ.  50,000 hours (Min)  Hardness: 7H, Anti-glare coating  Slim  Landscape
16:9  UHD 3840x2160  1.07B colors (10bit)  350 nits (typ.)  1200:1 (typ.) 5000:1 (DCR)  8ms  H = 178, V = 178 typ.  50,000 hours (Min)  Hardness: 7H, Anti-glare coating  Slim  Landscape
UHD 3840x2160  1.07B colors (10bit)  350 nits (typ.)  1200:1 (typ.) 5000:1 (DCR)  8ms  H = 178, V = 178 typ.  50,000 hours (Min)  Hardness: 7H, Anti-glare coating  Slim  Landscape
UHD 3840x2160  1.07B colors (10bit)  350 nits (typ.)  1200:1 (typ.) 5000:1 (DCR)  8ms  H = 178, V = 178 typ.  50,000 hours (Min)  Hardness: 7H, Anti-glare coating  Slim  Landscape
1.07B colors (10bit) 350 nits (typ.) 1200:1 (typ.) 5000:1 (DCR) 8ms H = 178, V = 178 typ. 50,000 hours (Min) Hardness: 7H, Anti-glare coating Slim Landscape
350 nits (typ.) 1200:1 (typ.) 5000:1 (DCR) 8ms H = 178, V = 178 typ. 50,000 hours (Min) Hardness: 7H, Anti-glare coating Slim Landscape
1200:1 (typ.) 5000:1 (DCR) 8ms H = 178, V = 178 typ. 50,000 hours (Min) Hardness: 7H, Anti-glare coating Slim Landscape
8ms H = 178, V = 178 typ. 50,000 hours (Min) Hardness: 7H, Anti-glare coating Slim Landscape
50,000 hours (Min) Hardness: 7H, Anti-glare coating Slim Landscape
50,000 hours (Min) Hardness: 7H, Anti-glare coating Slim Landscape
Hardness: 7H, Anti-glare coating Slim Landscape
Slim
Landscape
·
ADM 0 : AZOM 0 : AZOM
ARM Cortex-A73*4 + Cortex-A53*4
4GB
32GB
Ultra Fine Touch Techology (IR Recognition)
32768 ×32768
Windows: 40 points of touch, Android : 20 points of touch
2.0 x 3 (3840x2160 @60Hz, HDCP2.2, HDMI1 with CEC/ARC)
x1
x1
x 1 module slot
x1 (4K@60Hz)
x1 (Earphone out)
x1 (optical)
x2
2.0 x 2
3.0 x 4
x2, for touch
x1 ( DP 1.2, USB2.0, PD65W, Ethernet 100M)
mvViewBoard
myViewBoard  myViewBoard for Windows (Embedded in Windows Slot-in PC)
vCast/myViewBoard Display App
"SmartPort™ USB" to all channels.

Simple LAN sharing between IFP and slot-in device:

Light Sensor: POWER

**ERGONOMICS** Wall Mount (VESA® ):

Voltage: Consumption: Yes

100-240VAC +/- 10% Wide Range

95W(typ.), 0.5W (off)

600 mm x 400 mm

# **OPERATING CONDITIONS**

Temperature (° C):	0°C to 40°C
Humidity:	10% ~ 90% RH non-condensing

# DIMENSIONS (W X H X D)

Physical (inch / mm):	58.6 x 35.3 x 3.5 in / 1488 x 897 x 90 mm
-----------------------	---

65.7 x 39.8 x 8.8 in / 1669 x 1010 x Packaging (inch / mm): 223 mm

#### WEIGHT

Net (lb / kg): 89.3lb/40.5kg 109.6lb/49.7kg Gross (lb / kg):

## REGULATIONS

cTUVus, FCC/ICES003, Energy Star 8.0, EMC/CE, CB/LVD, GOST-R/EAC, UkrSEPRO, EPEAT, Mexico NOM, Mexico Energy, UKCA, UK-EEL, BSMI, BIS, LBL( Low Blue Light Certification), Flicker Free, Green BOM, ROHS, ErP-Eco, REACH, SCIP, WEEE, TPCH, Packing waste, CA65, PAIA

## **PACKAGE CONTENTS**

- 2. Remote control with AAA battery
- 3. Touch USB cable
- 4. Touch pen x 2

(VB-PEN-009)

- 5. Quick Start Guide + Compliance statement
- 6. RS232 adapter
- 7. Clamp x 5
- 8. Camera Plate
- 9. Screw x 8
- 10. HDMI cable

## **COMPATIBLE SLOT-IN PC**

- VPC2-O series VPC2-O-B series VPC25-W33-O1-1B VPC27-W53-O1-1B VPC12-WPO-17 VPC12-WPO-18