ViewSonic[®] Sector LS710-4KE

Key Features

- 3rd generation laser phosphor technology with up to a 30,000hour lifespan
- Designed for Xbox with 1440p
 @ 120Hz for an unrivaled gaming experience
- True 4K HDR immersive visual experience with up to a 300" screen
- 3,500 ANSI Lumens offering bright images in any environment
- High native contrast ratio through 0.65" DMD chip



Product **Description**

Transform any home into a cinematic experience with the LS710-4KE laser home projector. Adopting the 3rd generation laser phosphor technology with 3,500 ANSI Lumens and up to 30,000 hours lifespan, it delivers vibrant and bright visuals without the need for lamp replacement. This projector is designed for Xbox, supporting Xbox-exclusive resolution and refresh rate combinations for a seamless gaming experience. With the support of 1440p at a 120Hz refresh rate, it strikes a perfect balance of visual quality and fluidity that gamers love. Experience enhanced visual depth on a screen size of up to 300" with a high native contrast ratio through 0.65" DMD chip. The LS710-4KE features V lens shift, 1.36x optical zoom, H/V keystone, and 4 corner adjustment, allowing you to easily set up a big screen tailored to your preferences.



2. Zoom Ring





×

3. Keypad 4. Top IR 5. Front IR 6. Lens 7. Focus Ring 10. USB-A (5V/1.5A , Service) 11. 12V Trigger 12. Zoom Ring 13. Audio Out 14. DC In

Visit Us

www.viewsonic.com

SPECIFICATION		OTHERS	
Native Resolution:	3840x2160		Power adaptor:
Brightness:	3500 (ANSI Lumens)	Power Supply Voltage:	Input: 100~240V Output: 19.5VDC /
Contrast Ratio:	3,500,000:1		9.23A
Display Color:	1.07 Billion Colors	Power Consumption:	Normal: 180W Standby: <0.5W
Light Source Type:	Laser Phosphor	Operating Temperature:	0~40°C
Light Source Life (hours) with Normal Mode:	20000	Carton:	Brown
Light Source Life (hours) with SuperEco Mode:	30000 (Eco)	Net Weight:	3.30kg
		Gross Weight:	4.70kg
Lens:	F=2.51-2.93, f=15.985- 21.423mm	Dimensions (WxDxH) with Adjustment Foot:	286x216x129mm
Projection Offset:	137%+/-10%	Packing Dimensions:	400x280x155mm
Throw Ratio:	1.06-1.45	OSD Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, Arabic, Vietnamese, Greek, Norsk. Total 23
Optical Zoom:	1.36x		
Digital Zoom:	0.8x-2.0x		
Image Size:	30"-300"		
Throw Distance:	1-7m (100"@2.35m)		
Keystone:	H:+/-30° , V:+/-30°		
Lens Shift V. Range:	+15%, -0%		languages
Audible Noise (Normal):	31dB	User Guide Language:	English, S-Chinese, T- Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai,
Audible Noise (Eco):	26dB		
Input Lag:	4.2ms		
Resolution Support:	VGA(640 x 480) to 4K(3840 x 2160)		
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p	la	Vietnamese, total 20 languages
Horizontal Frequency:	15K-135KHz	STANDARD ACCESSORY	
Horizontal Frequency:		Power Cord:	1
Vertical Scan Rate:	23-240Hz	Remote Control:	1 (w/ backlit)
NFUI	2	QSG:	Yes
11) 1/11.	(HDMI 2.0/ HDCP 2.2)	Warranty:	*Warranty offered may differ from market to market
OUTPUT			
Audio-out (3.5mm):	1	OPTIONAL ACCESSORY	
Audio-out (HDMI ARC):	1 (eARC) (Share with HDMI Input)	Wall/Ceiling Mount:	PJ-WMK-007
Speaker:	15W	Carry Bag:	PJ-CASE-008
USB Type A (Power):	1 (5V/1.5A)		
12V Trigger (3.5mm):	1		
CONTROL			
RS232 (DB 9-pin male):	1		
USB Type A (Services):	1 (share with USB A Output)		