

SWA401

Wall Mount Powered Speakers



IN WALL CONTROL

Two 3.5mm stereo inputs, a 'dual-function' USB socket (charging and audio playback) plus volume control.

SWA401

Wall-Mount Loudspeakers, Amplifier & In-Wall Control System

40W

40w speaker output



Built in amplifier



Great sound from compact speakers



In-Wall & Remote Control

The SWA401 is a high efficiency, high output power audio solution that features an In-Wall amplifier and control surface, and is the perfect complement to interactive whiteboards or interactive flat panels.

The SWA401 is ideally suited to the education and corporate environments where high definition audio is a must-have; or where audio is poor and needs to be improved in a cost-effective way. It features two 3.5mm stereo inputs and a USB socket that has two functions; it can be used as a USB 5v charging output (for mobile, tablet and other portable devices), or for audio playback from flash drive - controlled from the remote control. Three year warranty as standard.

Three Digital Signal Processing (DSP) settings allows for exceptional audio reproduction making it versatile enough to use in small to large classrooms, meeting rooms and large halls.



SWA401

Wall Mount Powered Speakers

ConXeasy™ SWA401

Wall-Mount Loudspeakers, Amplifier & In-Wall Control System

The SWA401 is a high efficiency, high output power audio solution that is the perfect complement to interactive whiteboards or interactive flat panels. The SWA401 was developed based on the needs and feedback of customers looking for a cost-effective audio solution that featured In-Wall Control Surface (IWCS) flexibility, performance and high-quality sound.



Specifications

INPUTS (On In Wall Control System)

2x 3.5mm stereo mini-jacks : 20k ohms

USB: Playback of MP3/WMA/WAV files

OUTPUTS

USB: 5v charging of devices (Smartphone, Tablet etc.)

AMPLIFIERS

Continuous Average Output Power: 40W (20W x 2)

Both channels: 1kHz / 1% THD

Rated Distortion (1/2 power): 0.40%

Rated Impedance: 4 ohms

Frequency Response (50-20kHz): ± 2 dB

SPEAKERS

Mid-High Range : 1.5" Neodvmin x 1

Bass: 4" Ferrite driver x1

PERFORMANCE

Output power (RMS @ THD<40%) : 40W

Frequency response : 50 Hz - 25K Hz ± 2 dB

Dynamic Signal Processing : Speech / Hall / Music

CONTROL

In Wall Control System: Vol+ / Vol- / Source / Mode / Power

Remote Control keys : ON/OFF, MUTE, VOL+, VOL-, INPUT, SPEECH, HALL, MUSIC

AC POWER

External 19Volt DC Power Supply

Power Requirements: AC 230 - 240V - 50Hz

DIMENSIONS

Speakers (each): 160 x 150 x 240 mm (W, D, H)

In Wall Control System (each): 50 x 29 x 50 mm (W, D, H)

WHAT'S IN THE BOX

1x Pair Loudspeakers with Integral Wall Brackets

1x Amplifier/IWCS

1x Power Supply

1x Remote Control

Just Projectors,
Unit 7,
Campbell Court,
Bramley,
Hampshire,
RG26 5EG

conxeasy™