

Mercury Quad WUXGA

18,000 ANSI / 20,000 ISO Lumens | Contrast Ratio: 2,000:1 | Part No:117-779

MERCURY QUAD DIGITAL PROJECTOR



THE VISIONARIES CHOICE

Colour System:	DMD Specification:
3-chip DLP®	1920 x 1200 pixels native, +/- 12° tilt angle Fast transit pixels for smooth greyscale and improved contrast.
Display Type:	Aspect Ratio:
3 x 0.96" DarkChip™ DMD™	16x10 Fill Factor 87%

Key Features

Video & Graphics Processing

- DisplayPort accepts frame rates up to 120 Hz.
- 24p and 1080p native display.
- HDMI 1.4 for Side by Side, Frame Packing & Top Bottom 3D formats.
- Image enhancement for MPEG, Mosquito noise & color transients in composite sources.
- Dual Flash Processing can be used to multiply the displayed frame rate for 3D sources.
- Dual Pipe Processing: two sources in parallel for left and right eyes via HDMI.
- Synchronisation of active glasses or polarising switcher.
- Blend and warp processing.

HDBaseT® Interface

- Built in support for transmission of uncompressed High Definition Video over standard CAT5e/6 LAN cable.
- Allows projector to be placed up to 80m from source with low cost cabling.

Geometry Correction

- Cornerstone, Vertical & Horizontal Keystone, Pincushion & Barrel, Arc, and Image Rotation.
- Blanking control for custom input window sizing.
- Fit source aspect ratio to screen aspect ratio.
- Non-linear warp for curved screens via Projector Controller application.

Edge Blending

- Blending control of all sides with width control.
- Electronic black level compensation.
- Correction for non-active pixels at the edge of the display.

Picture in Picture

- Two sources can be displayed either one within the other (PIP), or side by side, with original aspect ratios maintained.

ColorMax™

- Accurate matching of projectors in tiled or blended applications.
- User selection and storage of primary and secondary color targets.

Projector Control

- Infra-red and wired remote.
- LAN control via protocol.
- Network control via hosted web page.
- Built-in ON/OFF timer for automatic start and switch off.
- Password Lamp Control.

Projector Controller Software

- Intuitive user interface for network control.
- Simultaneous control of user-defined groups of projectors.
- At-a-glance monitoring of projector status.

Source Compatibility:

HDMI including Deep Color™ processing and 3D standards.

3GSDI is SMPTE 292M, SMPTE 259M-C and SMPTE 424M compliant.

Graphics standards up to 1920 x 1200 resolution at 60Hz via HDMI and 120 Hz via DisplayPort.

Inputs/Outputs

Video & Computer			Communication & Control		
Type	Connector	Qty	Type	Connector	Qty
HDMI 1.4	HDMI	2	3D Sync Out	BNC	1
DisplayPort 1.1a	DisplayPort	1	3D Sync In	BNC	1
HDBaseT/LAN	RJ45	1	LAN (see HDBaseT)	RJ45	1
3G-SDI In	BNC	1	RS232	9-pin D Sub	1
3G-SDI Out	BNC	1	Wired Remote	3.5mm Stereo	1
			12V Trigger	Jack	2
				3.5mm Stereo	
				Jack	
			NOTE: The LAN port is shared with HDBase-T.		

3D Formats Supported	HDTV Formats Supported
Frame Packing	1080p (23.98Hz, 24Hz, 25Hz, 29.97Hz, 30Hz, 50Hz, 59.94Hz, 60Hz), 1080i (50Hz, 59.94Hz, 60Hz), 720p (50Hz, 59.94Hz, 60Hz)
Dual Pipe	
Frame Sequential	
Side By Side (half)	
Top and Bottom	

Computer Compatibility	Bandwidth
Up to 1920 x 1200 60Hz (HDMI/HDBaseT)	165 Megapixels per second on HDMI and DisplayPort
Up to 1920 x 1200 120Hz (DisplayPort)	295 Megapixels per second on DisplayPort

Remote Control	Automation Control
IR remote control, wireless and wired.	Crestron Room View® Connected
On-Board keypad	PJ Link
	LAN
	RS232
	AMX (Device Discovery)

Colour Temperature

User selectable from 3200 to 9000K

Lamp Type		Typical Lamp Life	
4 x 465W High Intensity Discharge		Full power: 2500 hours Eco mode: 3000 hours	
Lenses			
Lens	Part No.	Focus Range	Lens Shift
0.67:1 fixed HB	105-607	1.1m - 10m	Vert: 0.108 (U) 0.108 (D) frame, Hor: 0.044 (L) 0.044 (R) frame
1.12:1 fixed HB	105-608	3m - 15m	Vert: 0.567 (U) 0.45 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
1.16 - 1.49:1 zoom HB	109-236	3m - 15m	Vert: 0.408 (U) 0.408 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
1.39 - 1.87:1 zoom HB	105-610	4m - 24m	Vert: 0.567 (U) 0.45 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
1.87 - 2.56:1 zoom HB	105-611	4m - 24m	Vert: 0.567 (U) 0.45 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
2.56 - 4.16:1 zoom HB	105-612	9.1m - 45m	Vert: 0.567 (U) 0.45 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
4.16 - 6.96:1 zoom HB	105-613	12m - 80m	Vert: 0.567 (U) 0.45 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
6.92 - 10.36:1 zoom HB	109-235	12m - 80m	Vert: 0.567 (U) 0.45 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
Lens Mount			
Motorised and programmable shift, zoom and focus. Intelligent Lens Memory.			
Mechanical Mounting		Orientation	
Front/Rear Table		Table Top or Inverted: Yes	
Front/Rear Ceiling		Pointing Up: Yes	
Adjustable Front/Rear Feet		Pointing Down: Yes	
		Roll (Portrait): +/-10° from horizontal	
Power Requirements		Power Consumption	
110 - 240VAC 50/60Hz single phase		2300 W	
At 110V the projector runs a maximum of two lamps.			
Thermal Dissipation		Fan Noise	
7850 BTU/Hour		55 dBA	
Operating/Storage Temperature		Operating Humidity	
Operating: 0 to 35C (32 to 95F)		20% to 90% non-condensing	
Storage: -20 to 60C (-4 to 140F)			
Weight (Chassis Only)		Dimensions	
41 kg		L: 69.1 cm W: 51 cm H: 31 cm (excl. handle)	
90 lb		L: 27.2 in W: 20.1 in H: 12.2 in (excl. handle)	
Safety & EMC Regulations			
CE, FCC Class A, UL, CCC			
Accessories			
Accessory	Part No.		
Lamp & Housing	116-378		
4 Lamp & Housing incl. Filter Set	118-586		
Infrared Remote (replacement)	117-780		
Replacement Filter Set	116-847		
Rigging Frame	117-705		
<i>*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.</i>			
Downloads			
		User Guides	
		User Guides German	
		User Guides French	
		Important Information	



Certificate Number 13629
ISO 9001

Specifications subject to change without notice. Digital Projection version: - ©2016 Digital Projection.
DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc

DIGITAL PROJECTION, LTD GREENSIDE WAY, MIDDLETON MANCHESTER, UK. M24 1XX
T: +44.161.947.3300 | F: +44.161.684.7674 | www.digitalprojection.co.uk

DIGITAL PROJECTION, INC 55 CHASTAIN ROAD, SUITE 115 KENNESAW, GA. 30144
T: 770.420.1350 | F: 770.420.1360 | www.digitalprojection.com

DIGITAL PROJECTION, CHINA Rm A2006, ShaoYaoJu 101 North lane, Shi AO International Center, Chao Yang District, Beijing, 100029, PR CHINA
T: +86.10.58239771 | F: +86 10 58239770

DIGITAL PROJECTION, ASIA 16 NEW INDUSTRIAL ROAD, #02-10 HUDSON TECHNOCENTRE SINGAPORE 536204
T: +65.6284.1138 | F: +65.6284.1238

Just Projectors, Unit 7, Campbell Court, Bramley Hampshire, RG26 5EG